



# Single Split Wall Mounted Type



**Reinforced next-generation sterilizer!**  
Its effectiveness, even eliminating the AI virus, has been proven in three countries.



This unit can be easily installed in even the smallest spaces and offers exceptional cooling performance. Designed for low noise operation, it ensures a pleasant, cool environment. The "Jet Cool" feature provides speedy cooling and a clean air supply with the integrated Plasma Air Purifying System.



# Single Split Wall Mounted Type

Model			LS-C0964DM0	LS-C1264DM0	LS-C1865DM0	LS-C2665DM0
Capacity						
Cooling			9000	12000	18500	26000
Heating						
<b>Electrical Data</b>						
Voltage	Frequency/Phase	V,Hx $\phi$	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50
Power Input	Cooling/Heating	Watt	950	1300	1950	2700
Running Current	Cooling/Heating	A	4.2	5.8	8.5	12.6
<b>Installation</b>						
Net Dimensions	Indoor	mm	840 x 270 x 153	840 x 270 x 153	1090 x 300 x 180	1090 x 300 x 180
(WxHxD)	Outdoor	mm	717 x 498 x 228	717 x 498 x 228	801 x 555 x 262	840 x 577 x 276
Net Weight	Indoor / Outdoor	Kgs	7/25	7/25	13.5/38	13.5/50
Service Valve	Liquid Gas	$\phi$ (mm)	$1/4$ & $3/8$	$1/4$ & $1/2$	$1/4$ & $1/2$	$3/8$ & $5/8$

Model			LS-C306DGM1	LS-C366DGM1	LS-H0764DM0	LS-H0964DM0
Capacity						
Cooling			30000	36000	7000	9000
Heating					7700	9900
<b>Electrical Data</b>						
Voltage	Frequency/Phase	V,Hx $\phi$	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50
Power Input	Cooling/Heating	Watt	3150	4200	730/700	950/945
Running Current	Cooling/Heating	A	14.5	19	3.3/3.2	4.2/4.1
<b>Installation</b>						
Net Dimensions	Indoor	mm	1209 x 346 x 205	1209 x 346 x 205	840 x 270 x 153	840 x 270 x 153
(WxHxD)	Outdoor	mm	840 x 577 x 320	870 x 1060 x 320	717 x 497 x 228	717 x 498 x 228
Net Weight	Indoor / Outdoor	Kgs	18/75	18/80	7/25	7/25
Service Valve	Liquid Gas	$\phi$ (mm)	$1/4$ & $5/8$	$3/8$ & $5/8$	$1/4$ & $3/8$	$1/4$ & $3/8$

Model			LS-H1264DM0	LS-H1865DM0	LS-H2665DM0	LS-H306DGM1	LS-H306DGM1
Capacity							
Cooling			12000	18500	26000	32000	36000
Heating			13000	19800	26400	32000	36000
<b>Electrical Data</b>							
Voltage	Frequency/Phase	V,Hx $\phi$	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50	1 ~ 220/240/50
Power Input	Cooling/Heating	Watt	1300/1250	1990/1840	2700/2770	3150/3440	4200/3900
Running Current	Cooling/Heating	A	5.9/5.8	9.1/8.4	12.6	14.5/15.5	19/18
<b>Installation &amp; Stuffing</b>							
Net Dimensions	Indoor	mm	840X270X153	1090 x 300 x 180	1090 x 300 x 180	1209 x 346 x 205	1209 x 346 x 205
(WxHxD)	Outdoor	mm	717X498X228	840 x 577 x 276	840 x 577 x 276	870 x 800 x 320	870 x 1060 x 320
Net Weight	Indoor / Outdoor	Kgs	7/25	13.5/50	13.5/50	18/66	18/80
Service Valve	Liquid Gas	$\phi$ (mm)	$1/4$ & $1/2$	$1/4$ & $1/2$	$3/8$ & $5/8$	$1/4$ & $5/8$	$3/8$ & $5/8$





**Heat Exchanger from the Side**

**LG PLASMA**  
A water film allows for efficient and low noise air flow.

**Noise Reduction**



**Non-PLASMA**  
Water droplets hamper the air flow, causing noise.

**Energy Savings**



**Heat Exchanger from the Top**

**LG PLASMA**  
No water droplets

**Non-PLASMA**  
Water droplets causing corrosion and increasing energy consumption

Design and specifications are subject to change without prior notice for product improvement.

**LG Electronics South Africa (Pty) Ltd.**  
 LG House, 181 Barbara Road, Elandsfontein, Johannesburg  
 PO Box 473, Isando 1600, South Africa • Tel: (011) 571-6844 • Fax: (011) 571-6885  
[www.lge.co.za](http://www.lge.co.za)

**Contact numbers**  
 Cape Town: (021) 534-7950  
 Jhb. Toll Free: 0800 54 54 54  
 Durban: (031) 716-5454