



# Underceiling Type



**ONLY LV-B246BLA0 can be fitted floor level vertically.**

Depending on space availability, this model can be installed either on the ceiling or standing on the floor.

The vertical flow direction of the cool air can be controlled by remote control, and the low-noise design ensures a quiet and comfortably cool atmosphere.



**LG Air conditioning Toll Free: 0800 54 54 54**

# Underceiling Type

Model			LV-C368KLB0	LV-C488LLB0	LV-C 608LLB0	LV-B1864BL
Capacity						
Cooling			36000	47000	52000	19000
Heating						20000
Electrical Data						
Voltage	Frequency/Phase	V,Hx $\phi$	3 ~ 380/415/50	3 ~ 380/415/50	3 ~ 380/415/50	1 ~ 220/240/50
Power Input	Cooling/Heating	Watt	3470	4790	5670	1850/1850
Running Current	Cooling/Heating	A	6.3	8	10	9.2/9.2
Installation						
Net Dimensions	Indoor	mm	1452 x 315 x 750	1850 x 315 x 750	1850 x 315 x 750	1290 x 696 x 290
(WxHxD)	Outdoor	mm	1060 x 1140 x 440	1060 x 1220 x 455	1060 x 1220 x 455	1020 x 715 x 440
Net Weight	Indoor / Outdoor	Kgs	35/80	45/95	45/95	30/60
Service Valve	Liquid Gas	$\phi$ (mm)	1/4 & 5/8	3/8 & 3/4	3/8 & 3/4	1/4 & 1/2

Model			LV-B246BLA0	LV-H368KLB0	LV-H488LLB0	LV-H608LLB0
Capacity						
Cooling			24000	36000	47000	52000
Heating			24000	37000	51700	57000
Electrical Data						
Voltage	Frequency/Phase	V,Hx $\phi$	1 ~ 220/240/50	1 ~ 380/450/50	3 ~ 380/415/50	3 ~ 380/415/50
Power Input	Cooling/Heating	Watt	2670/2570	3470/3350	4790/4370	5670/5180
Running Current	Cooling/Heating	A	12.3/11.9	6.3/6.1	8.0/7.3	10/9.5
Installation						
Net Dimensions	Indoor	mm	1290 x 696 x 290	1450 x 315 x 750	1850 x 315 x 750	1850 x 315 x 750
(WxHxD)	Outdoor	mm	1020 x 715 x 440	1060 x 1140 x 440	1060 x 1120 x 455	1060 x 1200 x 455
Net Weight	Indoor / Outdoor	Kgs	30/60	35/80	45/95	45/95
Service Valve	Liquid Gas	$\phi$ (mm)	1/4 & 5/8	1/4 & 5/8	3/8 & 3/4	3/8 & 3/4

## Features

- Gold Fin™ Anti Corrosion
- Natural Wind By CHAOS Swing
- Wireless Remote Controlle
- Sleep Mode Auto Operation
- Auto Operation
- One-Touch Air Filter(Anti-Bacteria)
- Soft Dry Operation Mode
- Auto Restart
- Hot Start(Heat Pump)
- 24 Hour ON/OFF Setting Timer



Design and specifications are subject to change without prior notice for product improvement.

**LG Electronics South Africa (Pty) Ltd.**  
 LG House, 181 Barbara Road, Elandsfontein, Johannesburg  
 PO Box 473, Isando 1600, South Africa • Tel: (011) 571-6844 • Fax: (011) 571-6885  
[www.lge.co.za](http://www.lge.co.za)

## Airflow Direction Control



### Horizontal Airflow Direction Control. Manual Control

Adjust the horizontal airflow direction by manually moving the horizontal airflow direction louver by hand.



### Vertical Airflow Direction Control. Airflow Direction Control

The airflow direction can be adjust as desired by using the remote controller.

This is effective when you want to cool yourself directly.

### Contact numbers

Cape Town: (021) 534-7950  
 Jhb, Toll Free: 0800 54 54 54  
 Durban: (031) 716-5454